



IMPORTANT

Before the installation verify that all pannels of the mural fit perfectly .We advise you to be present during all the application process and to read well the instructions before beginning the installation.

Metylan® special



1.The application surface must be firm, clean, dry, without old wallpaper, dust, grease and oils.



3. Glue the mural with a brush or a roller and leave the mixture soak it thoroughly before the collocation.



2. Make the mixture carefully, following the instructions detailed below.



4. Place the photomural on the application wall or surface, taking care not to remain any air pockets. Once installed, wipe away immediately any excess of glue with a wet cloth.

Characteristics

Aspect : White powder
Density Bulk : 500 - 600 kg / m³.
Storage Time : 24 months (23°C / 55% H.R.).

Surface preparation



The surface must be firm, clean, dry and oilfree.
The cracks and fissures must be covered.
If there are fungus, these must be removed and the area

has to be treated with the appropriate fungicide.

On porous surfaces it is recommended to prepare the surface by applying a coat of primer with Metylan diluted with water according to the dosing chart. This way you will be able to remove easily the mural when you want to redecorate.

Mark the surface with a plumb line, using this as a starting point for the installation of the mural.

Preparation and application

Empty the necessary quantity of Metylan in cold water following the chart, shaking at the same time. Let it still for 30 minutes and shake it again vigorously.

Place the pannel or pannels upside down carefully.

Glue the strips with a brush or roller, then fold the strip from the tips towards the centre and let it still until the paper is totally soaked. Let it soften for 5 or 10 minutes before application.

Place the mural on the wall or application surface, hanging the top of the strip perfectly vertical, without folding the bottom. Brush from the centre to the edges to remove air bubbles.

Once you've verified the perfect placement on of the top, pull out the bottom and install it the same way.

After you've finished the installation, clean immediately any excess of the glue with a wet cloth.

Grams of glue square meters litres of water

Grams of glue	square meters	litres of water
25 grams	3 m2	0,5
50 grams	6 m2	1
100 grams	12 m2	2

Observations

Avoid air drafts while installing the photomural, as the glue will dry very quickly and the joints will tend to open.

If the room temperature is too low, the mural will dry slowly which can cause bubbles or discoloration of the mural.

Precautions

Keep away from children.

Don't throw away the product down the sewer.